



## PRODUCT DATA SHEET

### Walex Diesel SP C3 5w30

**Walex Diesel SP C3 5w30** is a modern high-tech synthetic motor oil created on the basis of high-quality base oil with the addition of the most modern additive packages that provide minimal sulfated ash, phosphorus and sulfur content in accordance with the requirements for low SAPS oils. **Walex Diesel SP C3 5w30** has excellent cold starting characteristics, heat/oxidation stability and helps maintain viscosity levels

#### Application:

Passenger cars with gasoline and diesel engines, including those equipped with T-GDI, CDI, TDI turbocharging systems, as well as complex exhaust gas treatment systems, which require the use of low-viscosity oils with C3 approval.

#### Features/Benefits:

- Synthetic oil
- DPF/Low SAPS
- Excellent engine protection
- Excellent anti-wear properties
- Preventing premature ignition of the mixture in the cylinders LSPI (Low Speed Pre-Ignition)
- Improved fuel efficiency and oil longevity
- Excellent lubricity at low temperatures

Viscosity	40°C	65.10
	100 °C	10.80
Viscosity index		158
Flash point (°C)		224
Pour point (°C)		-39
Density at 20°C		0.845
Base number		9.0
Sulfated ash content		0.75
CCS at -30°C		6120

#### Specification:

**Walex Diesel SP C3 5w30** Meets or exceeds the following specifications:

API SP, ACEA C3, VW 502 00/ 505 00/ 505 01 dexos2™ \* RN0700 / RN0710

